


Double Spring

BR**ER** Double Spring, ideal for the secure suspension of wire with hook or eye extensions in suspended ceiling installations suspended from a concrete slab. Special, pre-cut service holes Ø 3 mm to ensure a secure fixing of the wires.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Metal gauge: 0.6 mm



Standard Classification:

In compliance with EN 13964:2014




Advantages

- ✓ Quick and easy application
- ✓ The suspension height is regulated with the highest precision in a steady tie with a wire with hook or eye
- ✓ Minimized loss of useful space in the room
- ✓ Regulates the material consumption

Technical Data:


Steel Thickness	0.6 mm
Material fire reaction class:	A1
Corrosion resistance class:	B
Recommended load carrying capacity F	0.40 kN
Max. load carrying capacity admF	0.46 kN

Packaging and Storage:

- ✓ 100 units in every box. Packaged in distinctive green **BR****ER** boxes
- ✓ Store in a dry, covered and ventilated area

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

BR**ER** reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification.

MAY 2020