

## Brooer Wire with Hook and Eye

Brooer Wire with Hook and Eye, an ideal suspension between Rotary Hanger (respectively, the suspended ceiling construction) and concrete slab.



The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Available Sizes: 125, 250, 375, 500, 750, 1000 mm

Metal gauge: Ø 4 mm Ø 3 mm

### Standard Classification:

In compliance with EN 13964:2014



### Advantages:

- ✓ The suspension height is effortlessly and precisely regulated when paired with a Double Spring or Rotary Hanger
- ✓ Wire with Eye – eye diameter Ø 8 mm
- ✓ Quick and easy application

### Technical Data:

Parameters	
Reaction to fire	A1
Corrosion resistance class:	B
Recommended load carrying capacity F	0.40 kN
Max. load carrying capacity admF	0.46 kN

### Packaging and Storage:

Product	Length	Gauge	Bundle
Wire with Hook and Eye 125	125 mm	Ø 4mm & Ø 3 mm	100 pcs
Wire with Hook and Eye 250	250 mm	Ø 4mm & Ø 3 mm	100 pcs
Wire with Hook and Eye 375	375 mm	Ø 4mm & Ø 3 mm	100 pcs
Wire with Hook and Eye 500	500 mm	Ø 4mm & Ø 3 mm	100 pcs
Wire with Hook and Eye 750	750 mm	Ø 4mm & Ø 3 mm	100 pcs
Wire with Hook and Eye 1000	1000 mm	Ø 4mm & Ø 3 mm	100 pcs

- ✓ Packaged in distinctive Brooer Bundle
- ✓ Store in a dry, covered and ventilated area

### Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Brooer reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification.

May 2020